



# Tire Tag



## Dimensions

89mm x 5mm (max) x 1mm

## RF Specifications

### ISO 18000-b Compliant

- \* Memory: 2048 [bit]
- \* Frequency UHF
- \* North America: 902-928Mhz
- \* Europe: 865-868Mhz
- \* Japan: 950-956Mhz

### EPC Gen2 Compliant

- \* Memory: 96/512[bit]
- \* Frequency UHF
- \* North America: 902-928Mhz
- \* Europe: 865-868Mhz
- \* Japan: 950-956Mhz

## Temperature/Environmental (Typical minimum)

- \* Temperature Range: -40 to +70 °C (-40 to +148 °F)
- \* Storage Range: -51 to +95 °C (-60 to +203 °F)
- \* Molding Pressure: >50 Bar

[info@hanarfid.com](mailto:info@hanarfid.com)

Hana RFID  
2061 Case Pkwy South  
Twinsburg, OH 44223  
Tel (330) 405 4677  
Fax (330) 405-4623

[pbrown@hanarfid.com](mailto:pbrown@hanarfid.com)

Paul Brown – VP of Business Development  
Hana RFID  
2061 Case Pkwy South  
Twinsburg, OH 44223  
Tel (330) 405 4605  
Fax (330) 405-4623

[rklouda@hanarfid.com](mailto:rklouda@hanarfid.com)

Ralph Klouda – RFID Sales Manager  
Hana RFID  
2061 Case Pkwy South  
Twinsburg, OH 44223  
Tel (330) 405 4628  
Fax (330) 405-4623

H A N A R F I D